




SKF-SUDAMERICAN,S.A.



20 mm x 52 mm x 15 mm SKF 6304-Z deep groove ball bearings

Bearing No. 6304-Z

6304-Z Bearing 2D drawings and 3D CAD models

Size	52x20x15 mm
Bore Diameter	52 mm
Outer Diameter	20 mm
Width	15 mm
d	20 mm
D	52 mm
B	15 mm
d ₁	30.35 mm
D ₂	44.71 mm
r _{1,2} - min.	1.1 mm
d _a - min.	27 mm
d _a - max.	30.3 mm
D _a - max.	45 mm
r _a - max.	1 mm
Basic dynamic load rating - C	16.8 kN
Basic static load rating - C ₀	7.8 kN
Fatigue load limit - P _u	0.335 kN
Reference speed	30000 r/min
Limiting speed	19000 r/min
Calculation factor - k _r	0.03
Calculation factor - f ₀	12
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF



SKF-SUDAMERICAN,S.A.

Minimum Buy Quantity	N/A
Weight / Kilogram	0.15
EAN	7316577297723
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	6304-Z
Weight / LBS	0.33
Bore	0.787 Inch 20 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
d ₁	30.35 mm
D ₂	44.71 mm



SKF-SUDAMERICAN, S.A.

d_a min.	27 mm
d_a max.	30.3 mm
D_a max.	45 mm
r_a max.	1 mm
Basic dynamic load rating C	16.8 kN
Basic static load rating C_0	7.8 kN
Fatigue load limit P_u	0.335 kN
Calculation factor k_r	0.03
Calculation factor f_0	12
Mass bearing	0.15 kg