



# SKF-SUDAMERICAN,S.A.



71814 ACD/HCP4 Bearing 2D drawings and 3D CAD models

## 70 mm x 90 mm x 10 mm SKF 71814 ACD/HCP4 angular contact ball bearings

Bearing No. 71814 ACD/HCP4

Size	90x70x10 mm
Bore Diameter	90 mm
Outer Diameter	70 mm
Width	10 mm
d	70 mm
D	90 mm
B	10 mm
d <sub>1</sub>	76.7 mm
d <sub>2</sub>	76.7 mm
D <sub>1</sub>	83.5 mm
r <sub>1,2</sub> - min.	0.6 mm
r <sub>3,4</sub> - min.	0.3 mm
a	23.7 mm
d <sub>a</sub> - min.	73.2 mm
d <sub>b</sub> - min.	73.2 mm
D <sub>a</sub> - max.	86.8 mm
D <sub>b</sub> - max.	88 mm
r <sub>a</sub> - max.	0.6 mm
r <sub>b</sub> - max.	0.3 mm
d <sub>n</sub>	77.4 mm
Basic dynamic load rating - C	13 kN
Basic static load rating - C <sub>0</sub>	15 kN
Fatigue load limit - P <sub>u</sub>	0.64 kN
Limiting speed for grease	15000 r/min



## SKF-SUDAMERICAN,S.A.

Lubrication	
Limiting speed for oil lubrication	24000 mm/min
Ball - $D_w$	5.556 mm
Ball - $z$	31
$G_{ref}$	1.4 cm <sup>3</sup>
Calculation factor - $e$	0.68
Calculation factor - $Y_2$	0.87
Calculation factor - $Y_0$	0.38
Calculation factor - $X_2$	0.41
Calculation factor - $Y_1$	0.92
Calculation factor - $Y_2$	1.41
Calculation factor - $Y_0$	0.76
Calculation factor - $X_2$	0.67
Preload class A - $G_A$	117 N
Preload class B - $G_B$	350 N
Preload class C - $G_C$	700 N
Calculation factor - $f$	1.32
Calculation factor - $f_1$	0.97
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2B}$	1.09
Calculation factor - $f_{2C}$	1.17
Calculation factor - $f_{HC}$	1.02
Preload class A	169 N/micron
Preload class B	268 N/micron
Preload class C	368 N/micron
$d_1$	76.7 mm
$d_2$	76.7 mm
$D_1$	83.5 mm
$r_{1,2}$ min.	0.6 mm



## SKF-SUDAMERICAN,S.A.

$r_{3,4}$ min.	0.3 mm
$d_a$ min.	73.2 mm
$d_b$ min.	73.2 mm
$D_a$ max.	86.8 mm
$D_b$ max.	88 mm
$r_a$ max.	0.6 mm
$r_b$ max.	0.3 mm
$d_n$	77.4 mm
Basic dynamic load rating C	13 kN
Basic static load rating $C_0$	15 kN
Fatigue load limit $P_u$	0.64 kN
Attainable speed for grease lubrication	15000 r/min
Attainable speed for oil-air lubrication	24000 r/min
Ball diameter $D_w$	5.556 mm
Number of balls z	31
Reference grease quantity $G_{ref}$	1.4 cm <sup>3</sup>
Preload class A $G_A$	117 N
Static axial stiffness, preload class A	169 N/ $\mu$ m
Preload class B $G_B$	350 N
Static axial stiffness, preload class B	268 N/ $\mu$ m
Preload class C $G_C$	700 N
Static axial stiffness, preload class C	368 N/ $\mu$ m
Calculation factor f	1.32
Calculation factor $f_1$	0.97
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.09
Calculation factor $f_{2C}$	1.17
Calculation factor $f_{HC}$	1.02



## SKF-SUDAMERICAN,S.A.

Calculation factor e	0.68
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67
Mass bearing	0.12 kg